

Specification Sheet

Part Number: TAG62L-788



Laser Tag Label, 1.5" x .37", 125 Per Sheet, PET, White, 1000/pkg

Article Number

594-62788

Type

TAG62L

Color

White (WH)

Features & Benefits

- White polyester has a smooth surface, allowing for the highest resolution and print contrast.
- The acrylic-based adhesive bonds to a wide variety of substrates and resists abrasion.
- LaserTags are sheet fed for easy loading and fast printing.

Quantity Per

pack

Product Description	HellermannTyton white polyester labels are ideal for marking small electrical and electronic components, such as EPROMS', Integrated circuits, as well as the circuit board itself. Printed labels can withstand the soldering process and survive flux removal when the board is washed. HellermannTyton's 788 material is designed for use on flat surfaces and can also be used to identify connectors, buttons and just about anything requiring permanent, general purpose marking.
Short Description	Laser Tag Label, 1.5" x .37", 125 Per Sheet, PET, White, 1000/pkg
Global Part Name	TAG62L-788-WH
Width W (Imperial)	1.5
Width W (Metric)	38.1
Bundle Diameter Min (Imperial)	0.06
Bundle Diameter Min (Metric)	1.50
Thickness T (Metric)	64.0
Height H (Imperial)	0.375
Height H (Metric)	9.52
Material	Type 788, Polyester (788)
Material Shortcut	788

Adhesive	Acrylic
Halogen free	No
Adhesive Operating Temperature	-40°F to +199°F (-40°C to +93°C)
Operating Temperature (Metric)	-40°F to +199°F (-40°C to +93°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	1000
Package Quantity (Metric)	1000
Customs Number	3919905060
Labels per Column	25
Labels per Row	5
Weight (Metric)	0.521
Weight (Imperial)	1.14

