

Specification Sheet

Part Number: TAG2-100



Dot Matrix Label, Self-Laminating, .50" x .50" x 1.437", 16 Across, White, 5000/pkg

Article Number

595-02100

Type

TAG2

Color

White (WH)

Features & Benefits

- Dot matrix printable self-laminating vinyl has a smooth surface, allowing for the highest resolution and print contrast using an impact printer.
- The material is a conformable vinyl, allowing it to wrap and stay around wires and cable.
- The acrylic-based adhesive bonds to a wide variety of substrates and will remain in place long term.
- Tabtag dot matrix labels are specifically made for use in dot matrix printers for fast and easy printing.
- Labels come with a pin-feed margin to ensure that they can easily be loaded into any dot matrix printing system.

Quantity Per

pack

Product Description

HellermannTyton's self-laminating labels are used for marking wires and cable. The clear tail overlaps and protects the printed information from abrasion, chemicals and solvents and resists UV exposure. When printed using using any standard dot matrix printer, clear marking and high high-contrast imaging against the wire make this the perfect choice for durable identification.

Short Description

Dot Matrix Label, Self-Laminating, .50" x .50" x 1.437", 16 Across, White, 5000/pkg

Global Part Name

TAG2-100-WH

Local Order Number 2

595-02100

Fixation Method

Pasting / Stick

Variant

Adhesive label

Width W (Imperial)

0.5

Width W (Metric)

12.7

Bundle Diameter Min (Imperial)

0.15

Bundle Diameter Min (Metric)

3.80

Bundle Diameter Max (Imperial)

0.29

Bundle Diameter Max (Metric)

7.60

Thickness T (Metric)

75.0

Width of Liner (Metric)

228.60

Width of Liner (imperial)

8.9

Outside Diameter Max(Imperial) 0.299

Outside Diameter Min (metric) 3.8

Outside Diameter Min(Imperial) 0.149

Outside Diameter Max (metric) 7.60

Material Type 100, Vinyl (PVC), white (WH), self-laminating

Material Shortcut 100

Adhesive Acrylic

Halogen free No

Adhesive Operating Temperature -51°F to +200°F (-46°C to +93°C)

Operating Temperature (Metric) -51°F to +200°F (-46°C to +93°C)

Reach Complaint(Article 33) Yes

ROHS Complaint Yes

Certification/Specification WEB UL-Recognized

UL Recognized (US) Yes

Package Quantity(Imperial) 5000

Package Quantity (Metric) 5000

Customs Number 3919905060

Labels per Column 16

Labels per Row 16

Weight (Metric) 0.11

Weight (Imperial) 0.24