

## Specification Sheet

Part Number: TAG11T4-822C



Clear polyester is glossy, allowing for the highest resolution and print contrast.

The acrylic-based adhesive bonds to a wide variety of substrates and can withstand high temperatures long term.

Thermal Transfer Labels, .65" x .2", 4 Across, Polyester, Clear, 5000/roll

Article Number 596-00003

Type TAG11T4

Color Clear (CL)

Quantity Per roll

**Product Description** HellermannTyton transparent/clear polyester labels are ideal for marking products where the visibility of the label needs to be minimized, such as consumer products, where the color of the housing needs to remain as clean looking as possible. The clear material allows the surface color to blend in with the printed text. These labels can also be used as an over-laminate to provide further protection for printed text in extreme environments.

**Short Description** Thermal Transfer Labels, .65" x .2", 4 Across, Polyester, Clear, 5000/roll

Global Part Name	TAG11T4-822C-CL
Width W (Imperial)	0.65
Width W (Metric)	16.5
Bundle Diameter Min (Imperial)	.14
Bundle Diameter Min (Metric)	3.80
Bundle Diameter Max (Imperial)	0.29
Bundle Diameter Max (Metric)	7.37
Thickness T (Metric)	64.0
Height H (Imperial)	0.2
Height H (Metric)	5.08
Width of Liner (Metric)	66.04
Width of Liner (Imperial)	2.60
Material	Type 822C, Clear Polyester (822C)
Material Shortcut	822C

Adhesive	Acrylic
Halogen Free	No
Adhesive Operating Temperature	-51°F to +200°F (-46°C to +93°C)
Operating Temperature	-40°F to +302°F (-40°C to +150°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Certification/Specification	UL-Recognized
UL Recognized (US)	Yes
UL Recognized (US and Canada)	Yes
Package Quantity (Imperial)	5000
Package Quantity (Metric)	5000
Customs Number	3919102055
Labels per Column	1
Labels per Row	4

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)