

Specification Sheet

Part Number: 596-00206

**WARNING: PHOTOVOLTAIC
POWER SOURCE**

Solar Label, Reflective, 2017 Code, WARNING PHOTOVOLTAIC POWER SOURCE, 6.5" x 1.0", VL, Red, 50/pkg

Article Number	596-00206
Type	PVPSR
Color	Red (RD)
Features & Benefits	<ul style="list-style-type: none">•Made with UV-stable inks and materials for durability and weather resistance.•Reflective properties to meet applicable NEC code requirements for reflective identification.•Supplied with an aggressive adhesive to ensure long life.•Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.
Quantity Per	roll

Product Description

HellermannTyton Pre-Printed Solar Installation Labels are designed to meet the requirements of the National Electrical Code (NEC) and the International Fire Code (IFC) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV-stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

Short Description

Solar Label, Reflective, 2017 Code, WARNING PHOTOVOLTAIC POWER SOURCE, 6.5" x 1.0", VL, Red, 50/pkg

Global Part Name

PVPSR-242/552-RD

Technical Description

Pre-Printed Solar Label, Reflective, "WARNING: PHOTOVOLTAIC POWER SOURCE", 6.5" X 1", Red

Local Order Number 2

Cross Reference = 10 per pack: 596-00676

Width W (Imperial)

6.5

Width W (Metric)

165.1

Thickness T (Imperial)

0.0025

Thickness T (Metric)

64.0

Height H (Imperial)

1.0

Height H (Metric)

25.40

Width of Liner (Metric)

28.57

Width of Liner (imperial)

1.125

Material	Type 242/552, UV Stable Reflective Vinyl w/Acrylic Laminate
Material Shortcut	242/552
Adhesive	Acrylic
Halogen free	No
Adhesive Operating Temperature	-40°F to +302°F (-40°C to +150°C)
Operating Temperature (Metric)	-40°F to +174°F (-40°C to +79°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Certification/Specification WEB	NEC2011 UL 969 IFC 2012 NEC2017
Warranty (US)	Yes
UL Recognized (US)	Yes
Package Quantity(Imperial)	50
Package Quantity (Metric)	50
Customs Number	3919905060
Labels per Column	1
Labels per Row	1

Weight (Metric)

0.521

Weight (Imperial)

1.14