

Specification Sheet

Part Number: 596-00238

Made with UV-stable inks and materials for durability and weather resistance.

Polyester is resistant to chemicals and solvents and will remain legible in dirty environments.

High abrasion and scuff resistance for high-performance labeling.

Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.



Solar Label, Printable, Photovoltaic DC Disconnect, 3.75" x 1.0", PET, Red, 50/roll

Article Number 596-00238

Type DCDISCT

Color Red (RD)

Quantity Per roll

Product Description Designed with cross-laminated UV stable materials, these variable print solar installation labels are designed to accept printing from any standard thermal transfer printer using a resin-based ink ribbon for the best durability. Print your voltage information directly on the label and then laminate with an optional clear acrylic laminate material for added protection. These labels can be used to print disconnecting means and breaker series directly on the labels for a more professional result and a smoother inspection process.

| | |
|---------------------------|---|
| Short Description | Solar Label, Printable, Photovoltaic DC Disconnect, 3.75" x 1.0", PET, Red, 50/roll |
| Global Part Name | DCDISCT-840/281-RD |
| Local Order Number 2 | Cross Reference = 10 per pack: 596-00854; Printable Metal Solar Placard 5 pack: 596-00842; Engravable Metal Solar Placard 5 pack: 596-00858; Spanish version 50 per roll: 596-00814 |
| Width W (Imperial) | 3.75 |
| Width W (Metric) | 92.25 |
| Thickness T (Imperial) | 0.0025 |
| Thickness T (Metric) | 64.0 |
| Height H (Imperial) | 1.0 |
| Height H (Metric) | 25.4 |
| Width of Liner (Metric) | 98.29 |
| Width of Liner (Imperial) | 3.87 |
| Material | Type 840/281, Polyester, UV-stabilized, clear polyester laminate (840/281) |
| Material Shortcut | 840/281 |

| | |
|--------------------------------|--|
| Adhesive | Acrylic |
| Halogen Free | Yes |
| Adhesive Operating Temperature | -40°F to +302°F (-40°C to +150°C) |
| Operating Temperature | -40°F to +302°F (-40°C to +150°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Certification/Specification | NEC2017 NEC2014 CSA 66956 NEC2020 UL 969 IFC 2012 NEC2011 |
| Warranty (US) | Yes |
| UL Recognized (US) | Yes |
| Package Quantity (Imperial) | 50 |
| Package Quantity (Metric) | 50 |
| Customs Number | 3919102055 |
| Labels per Column | 1 |
| Labels per Row | 1 |

