

Specification Sheet

Part Number: 596-00240

Made with UV-stable inks and materials for durability and weather resistance.

Polyester is resistant to chemicals and solvents and will remain legible in dirty environments.

High abrasion and scuff resistance for high-performance labeling.

Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

| | |
|--------------------------------|--|
| RATED AC OPERATING CURRENT | |
| MAX RATED AC OPERATING CURRENT | |
| RATED AC OPERATING VOLTAGE | |
| MAX RATED AC OPERATING VOLTAGE | |
| RATED SHORT CIRCUIT CURRENT | |
| MAXIMUM SYSTEM VOLTAGE | |

Solar Label, Printable, DC BACKUP SYSTEM, 4.0" x 2.0", PET, Red, 50/roll

Article Number 596-00240

Type ACRATING

Color Red (RD)

Quantity Per roll

Product Description Designed with cross-laminated UV stable materials, these variable print solar installation labels are designed to accept printing from any standard thermal transfer printer using a resin-based ink ribbon for the best durability. Print your voltage information directly on the label and then laminate with an optional clear acrylic laminate material for added protection. These labels can be used to print disconnecting means and breaker series directly on the labels for a more professional result and a smoother inspection process.

| | |
|--------------------------------|--|
| Short Description | Solar Label, Printable, DC BACKUP SYSTEM, 4.0" x 2.0", PET, Red, 50/roll |
| Global Part Name | ACRATING-840/281-RD |
| Width W (Imperial) | 4.0 |
| Width W (Metric) | 101.6 |
| Thickness T (Imperial) | 0.0025 |
| Thickness T (Metric) | 64.0 |
| Height H (Imperial) | 2.0 |
| Height H (Metric) | 50.8 |
| Material | Type 840/281, Polyester, UV-stabilized, clear polyester laminate (840/281) |
| Material Shortcut | 840/281 |
| Adhesive | Acrylic |
| Halogen Free | Yes |
| Adhesive Operating Temperature | -40°F to +302°F (-40°C to +150°C) |
| Operating Temperature | -40°F to +302°F (-40°C to +150°C) |

| | |
|------------------------------|--|
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Certification/Specification | NEC2020 IFC 2012 NEC2011 NEC2017 UL 969 CSA 66956 NEC2014 |
| Warranty (US) | Yes |
| UL Recognized (US) | Yes |
| Package Quantity (Imperial) | 50 |
| Package Quantity (Metric) | 50 |
| Customs Number | 3919102055 |
| Labels per Column | 1 |
| Labels per Row | 1 |