

## Specification Sheet

Part Number: 596-00634



Pre-Printed Header Label, WARNING, 3.0" x 2.0", UV, PET, Orange, 250/roll

**Article Number**

596-00634

**Type**

3X2WARNINGUV

**Color**

Orange (OG)

**Features & Benefits**

- Preprinted Solar Labels are made with UV-stable inks and materials for durability, weather resistance and long-term outdoor use.
- Polyester is resistant to chemicals and solvents and will remain legible in dirty environments.
- High abrasion and scuff resistance for high performance labeling.
- Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

**Quantity Per**

roll

<b>Product Description</b>	These labels come with preprinted color headers so only one color of ribbon is needed to complete the message panel. Labels can be used with TagPrint® Pro label software and HellermannTyton thermal transfer printers to reduce labor, eliminate minimum orders and allow the user to create labels on demand.
<b>Short Description</b>	Pre-Printed Header Label, WARNING, 3.0" x 2.0", UV, PET, Orange, 250/roll
<b>Global Part Name</b>	3X2WARNINGUV-PET-OG
<b>Technical Description</b>	Pre-Printed Header Label, WARNING, 3" X 2", UV, Orange
<b>Width W (Imperial)</b>	3.0
<b>Width W (Metric)</b>	76.2
<b>Thickness T (Metric)</b>	64.0
<b>Height H (Imperial)</b>	2.0
<b>Height H (Metric)</b>	50.8
<b>Width of Liner (Metric)</b>	81.2
<b>Width of Liner (Imperial)</b>	3.2
<b>Material</b>	Polyester (PET)
<b>Material Shortcut</b>	PET

<b>Adhesive</b>	Acrylic
<b>Halogen Free</b>	No
<b>Adhesive Operating Temperature</b>	-40°F to +302°F (-40°C to +150°C)
<b>Operating Temperature</b>	-40°F to +302°F (-40°C to +150°C)
<b>Reach Compliant (Article 33)</b>	Yes
<b>ROHS Compliant</b>	Yes
<b>Certification/Specification</b>	NEC2020 CSA 66956 NEC2017 IFC 2012 NEC2011 NEC2014 ANSI Standard Z535.4 UL 969
<b>UL Recognized (US)</b>	Yes
<b>Package Quantity (Imperial)</b>	250
<b>Package Quantity (Metric)</b>	250
<b>Customs Number</b>	3919102055
<b>Labels per Column</b>	1
<b>Labels per Row</b>	1
<b>Weight (Metric)</b>	0.521
<b>Weight (Imperial)</b>	3.2

© 2021 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)