

Specification Sheet

Part Number: 596-00665



Solar Label, 2017 Code, WARNING DUAL POWER SOURCE...SYSTEM, 4.125 x .75, VL, Orange/White, 10/pkg

Article Number	596-00665
Type	WDPSLBL10
Color	Orange (OG)
Features & Benefits	<ul style="list-style-type: none"> •Pre-Printed Vinyl Solar Labels are made with UV-stable inks and materials for durability and weather resistance. •Supplied with an aggressive adhesive to ensure long life. •Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections. •Pre-printed labels offer significant time and cost savings over high priced plastic engraved phenolic placards and lead time purchased markers.
Quantity Per	pack

Product Description

HellermannTyton pre-printed vinyl Solar Installation Labels are designed to meet the requirements of the National Electrical Code and the International Fire Code as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV-stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

Short Description

Solar Label, 2017 Code, WARNING DUAL POWER SOURCE...SYSTEM, 4.125 x .75, VL, Orange/White, 10/pkg

Global Part Name

WDPSLBL10-443/552-OG

Technical Description

Solar Label, Warning- Dual Power Source Label, 4.12" X .75", Orange/White

Local Order Number 2

Cross Reference = 50 per roll: 596-00495; Metal Solar Placard 5 pack: 596-00833

Width W (Imperial)

4.12

Width W (Metric)

104.65

Thickness T (Metric)

64.0

Height H (Imperial)

0.75

Height H (Metric)

19.05

Material

Type 443/552, UV Stable Flexible White Vinyl with Acrylic Laminate

Material Shortcut

443/552

Adhesive	Acrylic
Halogen free	No
Adhesive Operating Temperature	-40°F to +174°F (-40°C to +79°C)
Operating Temperature (Metric)	-40°F to +174°F (-40°C to +79°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Certification/Specification WEB	UL 969 NEC2017
Warranty (US)	Yes
UL Recognized (US)	Yes
Package Quantity(Imperial)	10
Package Quantity (Metric)	10
Customs Number	3919102055
Labels per Column	1
Labels per Row	1
Weight (Metric)	0.521
Weight (Imperial)	3.2

© 2019 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)