

Specification Sheet

Part Number: 596-00666



Solar Label, CAUTION PHOTOVOLTAIC SYSTEM BACKFED, 4.12" x .75", VL, Yellow, 10/pkg

Article Number

596-00666

Type

CBACKFED10

Color

Yellow (YE)

Features & Benefits

- Made with UV-stable inks and materials for durability and weather resistance.
- Polyester is resistant to chemicals and solvents and will remain legible in dirty environments.
- Abrasion resistant for high-performance identification.
- Meets NEC and IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

Quantity Per

pack

Product Description	HellermannTyton makes it easier than ever for solar installers to meet PV labeling codes. Solar Label Convenience Packs allow installers to quickly and economically purchase high quality preprinted NEC 2014 and 2017 code-compliant solar installation labels. Packaged in 10-count quantities to meet the needs of smaller scale solar installations and independent contractors, Solar Label Convenience Packs are available in HellermannTyton's most popular preprinted NEC 2014 and 2017 code-compliant solar label formats. Each Solar Label Convenience Pack contains 10 solar installation labels. Choose from a variety of regular and reflective preprinted labels. For enhanced durability, clear laminate overlay labels are also available in a convenience pack.
Short Description	Solar Label, CAUTION PHOTOVOLTAIC SYSTEM BACKFED, 4.12" x .75", VL, Yellow, 10/pkg
Global Part Name	CBACKFED10-443/281-YE
Technical Description	Solar Label, Caution - PV System Backfed Label, 4.12" X .75", Yellow/White
Local Order Number 2	Cross Reference = 50 per roll: 596-00587; Metal Solar Placard 5 pack: 596-00834; Spanish version 50 per roll: 596-00827
Width W (Imperial)	4.12
Width W (Metric)	104.60
Thickness T (Imperial)	0.0025
Thickness T (Metric)	64.0
Height H (Imperial)	0.75
Height H (Metric)	19.05

Material	Type 443/281, UV-stabilized flexible white vinyl with clear polyester laminate (443/281)
Material Shortcut	443/281
Adhesive	Acrylic
Halogen Free	No
Adhesive Operating Temperature	-40°F to +174°F (-40°C to +79°C)
Operating Temperature	-40°F to +174°F (-40°C to +79°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Certification/Specification	NEC2017 NEC2020 UL 969 NEC2014
Warranty (US)	Yes
UL Recognized (US)	Yes
Package Quantity (Imperial)	10
Package Quantity (Metric)	10
Customs Number	3919905060

Labels per Column	1
Labels per Row	1
Weight (Metric)	.104
Weight (Imperial)	0.23

© 2021 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)