


Specification Sheet

Part Number: 596-00886



Solar Label, Reflective, 2017 Code, SOLAR PV SYSTEM...SHUTDOWN, 6.0" x 4.0", VL, Red, 50/pkg

Article Number	596-00886
Туре	RSDRD17
Color	Red (RD)
Features & Benefits	•Made with UV-stable inks and materials for durability and weather resistance. •Reflective properties to meet applicable NEC code requirements for reflective identification. •Supplied with an aggressive adhesive to ensure long life. •Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.
Quantity Per	pack

_				_					
ν	r۸	Иı	uct	11	20	cri	nt	10	۱n
	ıv	u	uvi	$\boldsymbol{\nu}$	63	UI I	v	٠.	,,,

HellermannTyton Pre-Printed Solar Installation Labels are designed to meet the requirements of the National Electrical Code (NEC) and the International Fire Code (IFC) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV-stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

Short Description

Solar Label, Reflective, 2017 Code, SOLAR PV SYSTEM...SHUTDOWN, 6.0" x 4.0", VL, Red, 50/pkg

Global Part Name

RSDRD17-242/552-RD

Technical Description

Pre-Printed Solar Label, Reflective-2017 Code, Rapid Shutdown Label - Roof Hazard, 6.0" X 4.0", Vinyl, Yellow, 50/RL

Length L (Metric)

101.6

Width W (Imperial)

6.0

Width W (Metric)

152.4

Thickness T (Metric)

64.0

Height H (Imperial)

4.0

Height H (Metric)

101.60

Material

Type 242/552, UV Stable Reflective Vinyl w/Acrylic Laminate

Material Shortcut

242/552

Adhesive	Acrylic			
Halogen free	No			
Adhesive Operating Temperature	-40°F to +302°F (-40°C to +150°C)			
Operating Temperature (Metric)	-40°F to +174°F (-40°C to +79°C)			
Reach Complaint(Article 33)	Yes			
ROHS Complaint	Yes			
Certification/Specification WEB	NEC2017			
Warranty (US)	Yes			
UL Recognized (US)	Yes			
Package Quantity(Imperial)	50			
Package Quantity (Metric)	50			
Customs Number	3919102055			
Labels per Column	1			
Labels per Row	1			
Weight (Metric)	.104			
Weight (Imperial)	0.23			

