

## Specification Sheet

Part Number: 596-00904



**Arc Flash Hazard  
Appropriate PPE Required**

Do not operate controls or open covers without appropriate personal protection equipment.

Failure to comply may result in injury or death!

Refer to NFPA 70E for minimum PPE requirements.



HellermannTyton 596-00904

Arc Flash Label, DANGER APPROPRIATE PPE REQUIRED, 5.0" x 3.75", PET, Red/White, 10/pkg

**Article Number** 596-00904

**Type** AF5X35D

**Color** Red (RD)

### Features & Benefits

- Made with UV-stable inks and materials for durability and weather resistance.
- Polyester is resistant to chemicals and solvents and will remain legible in dirty environments.
- High abrasion and scuff resistance for high-performance labeling.
- Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

**Quantity Per** pack

|                               |   |
|-------------------------------|---|
| <b>Product Description</b>    | HellermannTyton makes it easier than ever for solar installers to meet PV labeling codes. Solar Label Convenience Packs allow installers to quickly and economically purchase high quality preprinted NEC 2014, 2017 and 2020 code-compliant solar installation labels. Packaged in 10-count quantities to meet the needs of smaller scale solar installations and independent contractors, Solar Label Convenience Packs are available in HellermannTyton's most popular preprinted NEC 2014, 2017 and 2020 code-compliant solar label formats. Each Solar Label Convenience Pack contains 10 solar installation labels. Choose from a variety of regular and reflective preprinted labels. For enhanced durability, clear laminate overlay labels are also available in a convenience pack. |
| <b>Short Description</b>      | Arc Flash Label, DANGER APPROPRIATE PPE REQUIRED, 5.0" x 3.75", PET, Red/White, 10/pkg  |
| <b>Global Part Name</b>       | AF5X35D-840/281-RD  |
| <b>Technical Description</b>  | Arc Flash Label, Danger- Appropriate PPE required, 5.0" X 3.75", Red/White  |
| <b>Width W (Imperial)</b>     | 5.00  |
| <b>Width W (Metric)</b>       | 127   |
| <b>Thickness T (Imperial)</b> | 0.0025  |
| <b>Thickness T (Metric)</b>   | 64.0  |
| <b>Height H (Imperial)</b>    | 3.75  |
| <b>Height H (Metric)</b>      | 95.25   |

|  |  |
|--|--|
| <b>Material</b>                        | Type 840/281, Polyester, UV-stabilized, clear polyester laminate (840/281) |
| <b>Material Shortcut</b>               | 840/281  |
| <b>Adhesive</b>                        | Acrylic  |
| <b>Halogen free</b>                    | Yes  |
| <b>Adhesive Operating Temperature</b>  | -40°F to +302°F (-40°C to +150°C)  |
| <b>Operating Temperature (Metric)</b>  | -40°F to +302°F (-40°C to +150°C)  |
| <b>Reach Complaint(Article 33)</b>     | Yes  |
| <b>ROHS Complaint</b>                  | Yes  |
| <b>Certification/Specification WEB</b> | NEC2011 NEC2017 NEC2014 NEC2020  |
| <b>Warranty (US)</b>                   | Yes  |
| <b>UL Recognized (US)</b>              | Yes  |
| <b>Use Conditions</b>                  | For Indoor Use Only  |
| <b>Package Quantity(Imperial)</b>      | 10   |
| <b>Package Quantity (Metric)</b>       | 10   |
| <b>Labels per Column</b>               | 1  |

|                          |       |
|--------------------------|-------|
| <b>Labels per Row</b>    | 1     |
| <b>Weight (Metric)</b>   | 0.521 |
| <b>Weight (Imperial)</b> | 1.14  |