

## Specification Sheet

Part Number: 596-01003

Made with UV-stable inks and materials for durability and weather resistance.

Polyester is resistant to chemicals and solvents and will remain legible in dirty environments.

Abrasion resistant for high-performance identification.

Meets NEC and IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.



Solar Label, Reflective, RAPID SHUTDOWN FOR SOLAR PV SYSTEM, 6.5" X 1.0", VL, Red, 50/roll

Article Number 596-01003

Type RSSPVS

Color Red (RD)

Quantity Per roll

**Product Description** HellermannTyton Pre-Printed Vinyl Solar Installation Labels are designed to meet the requirements of the National Electrical Code and the International Fire Code as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV-stable materials and adhesives designed to stick to both baked enamel and powder coated surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

Short Description Solar Label, Reflective, RAPID SHUTDOWN FOR SOLAR PV SYSTEM, 6.5" X 1.0", VL, Red, 50/roll

Global Part Name RSSPVS-505/281-RD

Width W (Imperial) 6.5

Width W (Metric) 165.1

Thickness T (Imperial) 0.0025

Thickness T (Metric) 64.0

Height H (Imperial) 1.0

Height H (Metric) 25.40

Width of Liner (Metric) 28.57

Width of Liner (Imperial) 1.125

Material Type 505/281, UV-stabilized reflective vinyl with clear polyester laminate (505/281)

Material Shortcut 505/281

Adhesive Acrylic

Halogen Free No

Adhesive Operating Temperature	-40°F to +302°F (-40°C to +150°C)
Operating Temperature	-40°F to +174°F (-40°C to +79°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Certification/Specification	NEC2020 UL 969
UL Recognized (US)	Yes
Package Quantity (Imperial)	50
Package Quantity (Metric)	50
Customs Number	3926909988
Labels per Column	1
Labels per Row	1