


Specification Sheet

Part Number: 596-01005

NOMINAL ESS AC VOLTAGE:	<input type="text"/>
MAXIMUM ESS DC VOLTAGE:	<input type="text"/>
AVAILABLE FAULT CURRENT DERIVED FROM THE ESS	<input type="text"/>
DATE CALCULATION PERFORMED:	<input type="text"/>

596-00997 

Solar Label, Printable, ENERGY STORATE SYSTEM RATING LABEL, 3.75" X 2.12", PET, Red, 10/pkg

Article Number

596-01005

Type

ESS202010

Color

Red (RD)

Features & Benefits

- Made with UV-stable inks and materials for durability and weather resistance.
- Polyester is resistant to chemicals and solvents and will remain legible in dirty environments.
- High abrasion and scuff resistance for high-performance labeling.
- Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

Quantity Per

pack

Product Description	HellermannTyton makes it easier than ever for solar installers to meet PV labeling codes. Solar Label Convenience Packs allow installers to quickly and economically purchase high quality preprinted NEC 2014, 2017 and 2020 code-compliant solar installation labels. Packaged in 10-count quantities to meet the needs of smaller scale solar installations and independent contractors, Solar Label Convenience Packs are available in HellermannTyton's most popular preprinted NEC 2014, 2017 and 2020 code-compliant solar label formats. Each Solar Label Convenience Pack contains 10 solar installation labels. Choose from a variety of regular and reflective preprinted labels. For enhanced durability, clear laminate overlay labels are also available in a convenience pack.
Short Description	Solar Label, Printable, ENERGY STORATE SYSTEM RATING LABEL, 3.75" X 2.12", PET, Red, 10/pkg
Global Part Name	ESS202010-840/281-RD
Width W (Imperial)	3.75
Width W (Metric)	92.25
Thickness T (Imperial)	0.0025
Thickness T (Metric)	64.0
Height H (Imperial)	2.1
Height H (Metric)	53.34
Width of Liner (Metric)	98.29
Width of Liner (imperial)	3.87

Material	Type 840/281, Polyester, UV-stabilized, clear polyester laminate (840/281)
Material Shortcut	840/281
Adhesive	Acrylic
Halogen free	Yes
Adhesive Operating Temperature	-40°F to +302°F (-40°C to +150°C)
Operating Temperature (Metric)	-40°F to +302°F (-40°C to +150°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Certification/Specification WEB	UL 969 NEC2017 CSA 66956
UL Recognized (US)	Yes
Package Quantity(Imperial)	10
Package Quantity (Metric)	10
Customs Number	3919102055
Labels per Column	1
Labels per Row	1

Weight (Metric) 0.104

Weight (Imperial) 0.23