

Specification Sheet

Part Number: 596-01040

**RAPID SHUTDOWN FOR
SOLAR PV SYSTEM**

Solar Label, Reflective, RAPID SHUTDOWN FOR SOLAR PV SYSTEM, 6.5" X 1.0", V, Red, 10/pkg

Article Number 596-01040

Type RSSPVS10

Color Red (RD)

Features & Benefits

- Made with UV-stable inks and materials for durability and weather resistance.
- Polyester is resistant to chemicals and solvents and will remain legible in dirty environments.
- Abrasion resistant for high-performance identification.
- Meets NEC and IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

Quantity Per pack

Product Description	HellermannTyton makes it easier than ever for solar installers to meet PV labeling codes. Solar Label Convenience Packs allow installers to quickly and economically purchase high quality preprinted NEC 2014, 2017 and 2020 code-compliant solar installation labels. Packaged in 10-count quantities to meet the needs of smaller scale solar installations and independent contractors, Solar Label Convenience Packs are available in HellermannTyton's most popular preprinted NEC 2014, 2017 and 2020 code-compliant solar label formats. Each Solar Label Convenience Pack contains 10 solar installation labels. Choose from a variety of regular and reflective preprinted labels. For enhanced durability, clear laminate overlay labels are also available in a convenience pack.
Short Description	Solar Label, Reflective, RAPID SHUTDOWN FOR SOLAR PV SYSTEM, 6.5" X 1.0", V, Red, 10/pkg
Global Part Name	RSSPVS10-505/281-RD
Width W (Imperial)	6.5
Width W (Metric)	165.1
Thickness T (Imperial)	0.0025
Thickness T (Metric)	64.0
Height H (Imperial)	1.0
Height H (Metric)	25.40
Width of Liner (Metric)	28.57
Width of Liner (imperial)	1.125

Material	Type 505/281, UV-stabilized reflective vinyl with clear polyester laminate (505/281)
Material Shortcut	505/281
Adhesive	Acrylic
Halogen free	No
Adhesive Operating Temperature	-40°F to +174°F (-40°C to +79°C)
Operating Temperature (Metric)	-40°F to +174°F (-40°C to +79°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Certification/Specification WEB	UL 969 NEC2020
UL Recognized (US)	Yes
Package Quantity(Imperial)	10
Package Quantity (Metric)	10
Customs Number	3919905060
Labels per Column	1
Labels per Row	1

Weight (Metric) 0.104

Weight (Imperial) 0.23