

## Specification Sheet

Part Number: 596-12203



Convenient tab is easier to remove from the liner, speeding labeling operations.

Tab acts as a guide during positioning or repositioning to ensure a straight wrap and a high-quality appearance.

Tab helps prevent label slippage when applied to cable insulation, reducing labor.

In tests, TabTags increased the average number of wraps per hour by 12 percent, saving time and increasing output.

Thermal Transfer Tab Label, Self-Laminating, 0.5 x 0.37 x 0.82", Vinyl, White, 10M/RL

Article Number 596-12203

Type TAG26T6ES

Color White (WH)

Quantity Per reel

**Product Description**

HellermannTyton TabTag thermal transfer self-laminating labels are a conformable vinyl film with a white printable surface followed by a clear tail that laminates the printed text when applied to a wire or cable. Handling the label by the tab helps keep fingers off the clear overlay, ensuring years of performance. The labels are UL recognized for indoor use with an aggressive acrylic adhesive that enables the label to bond to large and small diameter wires.

|                                |   |
|--------------------------------|---|
| Short Description              | Thermal Transfer Tab Label, Self-Laminating, 0.5 x 0.37 x 0.82", Vinyl, White, 10M/RL |
| Global Part Name               | TAG26T6ES-100B-WH   |
| Width W (Imperial)             | 0.5   |
| Width W (Metric)               | 12.70   |
| Bundle Diameter Min (Imperial) | 0.10  |
| Bundle Diameter Min (Metric)   | 2.54  |
| Bundle Diameter Max (Imperial) | 0.17  |
| Bundle Diameter Max (Metric)   | 4.32  |
| Height H (Imperial)            | 0.37  |
| Height H (Metric)              | 9.39  |
| Width of Liner (Metric)        | 101.6   |
| Width of Liner (Imperial)      | 4.00  |
| Material                       | Type 100B, Vinyl, white transparent, self-laminating (100B)                           |
| Material Shortcut              | 100B  |

|                                |                                  |
|--------------------------------|----------------------------------|
| Adhesive                       | Acrylic                          |
| Halogen Free                   | Yes                              |
| UV Resistant (Yes/No)          | Yes                              |
| Adhesive Operating Temperature | -40°F to +205°F (-40°C to +96°C) |
| Operating Temperature          | -40°F to +205°F (-40°C to +96°C) |
| Reach Compliant (Article 33)   | Yes                              |
| ROHS Compliant                 | Yes                              |
| UL Recognized (US)             | Yes                              |
| UL Recognized (US and Canada)  | Yes                              |
| Package Quantity (Imperial)    | 10000                            |
| Package Quantity (Metric)      | 10000                            |
| Customs Number                 | 3919102055                       |
| Labels per Row                 | 6                                |

## About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global

customers. HellermannTyton operates in 40 countries, with North American headquarters in Milwaukee, Wisconsin.  
([www.hellermann.tyton.com](http://www.hellermann.tyton.com)).

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)