

Specification Sheet

Part Number: FCSCSM

Use with epoxy or anaerobic adhesives for different applications or user preference.

Pre-radiused zirconia ceramic ferrules provide precision installation.

Meet ANSI/TIA/EIA 568-C standards.

Meet ANSI/TIA/EIA 604 (FOCIS) connector interface requirements.



Connector, Fiber Optic SC Singlemode 900µm, 2mm, 3mm (Blue) Simplex–Epoxy & Polish, 1/Pkg

Article Number 855-14202

Type FCSCSM

Color Blue (BU)

Quantity Per bag

Product Description Our epoxy/anaerobic connectors are designed for field or factory installation, using either epoxy or anaerobic adhesives. These connectors are made with pre-radiused zirconia ceramic ferrules to provide precision alignment and installation. Epoxy adhesives provide affordable and reliable connections with lowest losses (less than 0.5dB). The epoxy can be allowed to set overnight or cured in an inexpensive oven. Anaerobic adhesives can be used with accelerators for faster curing

Short Description	Connector, Fiber Optic SC Singlemode 900µm, 2mm, 3mm (Blue) Simplex–Epoxy & Polish, 1/Pkg
Global Part Name	FCSCSM
Technical Description	SC Single Mode Fiber Connector, Blue
Port Count	1
Material	Plastic (PL)
Material Shortcut	PL
Package Quantity (Imperial)	1
Package Quantity (Metric)	1
Customs Number	8536700000