

Specification Sheet

Part Number: FCST



Use with epoxy or anaerobic adhesives for different applications or user preference.

Pre-radiused zirconia ceramic ferrules provide precision installation.

Meet ANSI/TIA/EIA 568-C standards.

Meet ANSI/TIA/EIA 604 (FOCIS) connector interface requirements.

Connector, Fiber Optic ST Multimode 900µm, 2mm, 3mm Simplex–Epoxy & Polish, 1/Pkg

Article Number 855-14203

Type FCST

Color Black (BK)

Quantity Per bag

Product Description Our epoxy/anaerobic connectors are designed for field or factory installation, using either epoxy or anaerobic adhesives. These connectors are made with pre-radiused zirconia ceramic ferrules to provide precision alignment and installation. Epoxy adhesives provide affordable and reliable connections with lowest losses (less than 0.5dB). The epoxy can be allowed to set overnight or cured in an inexpensive oven. Anaerobic adhesives can be used with accelerators for faster curing

Short Description Connector, Fiber Optic ST Multimode 900µm, 2mm, 3mm Simplex–Epoxy & Polish, 1/Pkg

Global Part Name FCST

Technical Description ST Multimode Fiber Connector

Port Count 1

Material Metal (MET)

Material Shortcut MET

Package Quantity (Imperial) 1

Package Quantity (Metric) 1

Customs Number 8536700000