

## Specification Sheet

Part Number: PFCSC10G

Factory-polished zirconia ceramic ferrules for quick and reliable field installations.

Unique wedge clip retains connector shape for precision connection.

Easy to use- no epoxy, heat curing, polishing or special tools required.

Color coded for easy identification.

Meet ANSI/TIA/EIA 568-C standards.

Meet ANSI/TIA/EIA 604 (FOCIS) connector interface requirements.



Connector, Fiber Optic SC Multimode OM3 (50/125), Pre-Polished (Cleave & Insert), 1/Pkg

**Article Number** 855-14217

**Type** PFCSC

**Color** Aqua (AE)

**Quantity Per** bag

**Product Description** Pre-polished connectors provide high performance and eliminate the need for the time consuming task of hand polishing ferrules in the field. A factory pre-cleaved fiber stub and index-matching gel combine to offer an immediate low loss termination of single mode or multimode fiber.

<b>Short Description</b>	Connector, Fiber Optic SC Multimode OM3 (50/125), Pre-Polished (Cleave & Insert), 1/Pkg
<b>Global Part Name</b>	PFCSC
<b>Technical Description</b>	Pre-Polished SC 10G 50/125 Multimode Fiber Connector, Aqua
<b>Port Count</b>	2
<b>Width W (Metric)</b>	28
<b>Height H (Metric)</b>	9.3
<b>Package Quantity (Imperial)</b>	1
<b>Package Quantity (Metric)</b>	1
<b>Customs Number</b>	8536700000