

Specification Sheet

Part Number: CCE-1111SX-B



Customer Connection Enclosure, 1x SC Adapter SM, Black, 1/pkg

Article Number

857-01436

Type

CCE-A11121SX1/BK

Color

Black (BK)

Features & Benefits

- Black, UV stable enclosure with IP54 (NEMA 3S) sealing rating for long-term outdoor performance.
- Internal positive fiber management and fiber retention clips maintain a minimum 30 mm bend radius throughout, ensuring reliable data throughput.
- Hinged lid allows quick and clear access to internal fiber for splicing and termination.
- CCE is same width as a brick blow-out cover to mask any bricks damaged by drilling.

Quantity Per

EA

Product Description

The Customer Connection Enclosure (CCE) is a Building Entry Point (BEP), providing a fiber termination and network demarcation point external to the connected premise in a Fiber to the Home (FTTH) network. In addition to providing an external test point, the enclosure stores up to 50 m of 1.1 mm cable. A loop-through facility allows for single fiber elements to be removed and spliced while the remaining fiber can be fed on to the next connection point. A single port in the rear of the closure allows fiber to be passed through the wall into the customer premises. Supplied cable ties secure all incoming/outgoing cables/blown fiber ducts and provide strain relief where necessary. The CCE can be supplied pre-loaded with fiber adapters and pigtails as required. •2x SC Simplex/LC Duplex customer connections for redundancy or multiple connections. •4x heat shrink splices accommodate connections to the adapters or drop cables. •6 incoming/outgoing ports and through-the-wall port to support multiple incoming and drop cables up to 7 mm in diameter. •Can store up to a maximum of 50 m of 1.1 mm cable.

Short Description

Customer Connection Enclosure, 1x SC Adapter SM, Black, 1/pkg

Global Part Name

CCE-A11121SX1/BK

Technical Description

The Customer Connection Enclosure (CCE) supports a maximum 2 x SC Simplex or LC Duplex adaptors. The closure is manufactured from UV stable ABS with a hinged lid which locks in the open position to allow for quick and clear access to the internal fibre. The closure has 6 entry/exit ports at the bottom of the closure which are suitable for cables and ducts up to a maximum diameter of 8.5mm. A loop through facility allows for single fibre elements to be removed and spliced whilst the remaining fibres can be fed on to the next connection point. A single port in the rear of the closure allows for fibre to be passed through the wall into the customer premises. Mechanical fixing is provided to secure all incoming/outgoing cables/blown fibre ducts and to provide strain relief where necessary. Internal positive fibre management and fibre retention clips maintain a minimum 30mm bend radius throughout for up to a maximum of 50m of 1.1mm diameter cable.

Contents of pkg/kit

CCE Enclosure, Black Foam Sealing grommets 3x Wall mounting screw and anchor 3x Red cable tie Phillips screw lock 1x SC SM Adapter

Variant

Outdoor FTTx Enclosures

Width W (Imperial)

5.12

Width W (Metric)

130

Height H (Imperial) 10.35

Height H (Metric) 263

Depth D (imperial) 1.46

Depth D (metric) 37

Material Acrylonitrile Butadiene Styrene, UV-stabilized (ABSUV)

Material Shortcut ABS

Package Quantity(Imperial) 1

Package Quantity (Metric) 1

Customs Number 8536700000