

Specification Sheet

Part Number: CCE-1111AX-G



Customer Connection Enclosure, 1x LC/APC Duplex SM, Gray, 1/pkg

Article Number

857-01448

Type

CCE-A11121AX1/GY

Color

Gray (GY)

Features & Benefits

- UV stable enclosure with IP54 (NEMA 3S) sealing rating for long-term outdoor performance.
- Internal positive fiber management and fiber retention clips maintain a minimum 30 mm bend radius throughout, ensuring reliable data throughput.
- Hinged lid allows quick and clear access to internal fiber for splicing and termination.
- CCE is same width as a brick blow-out cover to mask any bricks damaged by drilling.

Quantity Per

EA

Product Description

The Customer Connection Enclosure (CCE) is designed as a Building Entry Point (BEP) to provide a fiber termination and network demarcation point in a Fiber to the Home (FTTH) network. A loop-through facility allows single fiber elements to be removed and spliced while remaining fiber can be fed on to the next connection point. A single port in the rear allows fiber to be passed through the wall into the customer premises. Supplied cable ties secure all incoming/outgoing cables and blown fiber ducts and provide strain relief where necessary. The CCE can be supplied pre-loaded with fiber adapters and pigtails as required. •2x SC Simplex/LC Duplex customer connections •4x heat shrink splices •6x incoming/outgoing ports and through-the-wall port •Suitable for cables or ducts up to a maximum diameter of 7 mm •Store up to a maximum of 50 m of 1.1 mm cable

Short Description

Customer Connection Enclosure, 1x LC/APC Duplex SM, Gray, 1/pkg

Global Part Name

CCE-A11121AX1/GY

Technical Description

The Customer Connection Enclosure (CCE) supports a maximum 2 x SC Simplex or LC Duplex adaptors. The closure is manufactured from UV stable ABS with a hinged lid which locks in the open position to allow for quick and clear access to the internal fibre. The closure has 6 entry/exit ports at the bottom of the closure which are suitable for cables and ducts up to a maximum diameter of 8.5mm. A loop through facility allows for single fibre elements to be removed and spliced whilst the remaining fibres can be fed on to the next connection point. A single port in the rear of the closure allows for fibre to be passed through the wall into the customer premises. Mechanical fixing is provided to secure all incoming/outgoing cables/blown fibre ducts and to provide strain relief where necessary. Internal positive fibre management and fibre retention clips maintain a minimum 30mm bend radius throughout for up to a maximum of 50m of 1.1mm diameter cable.

Contents of pkg/kit

CCE Enclosure, Gray Foam Sealing grommets 3x Wall mounting screw and anchor 3x Red cable tie Phillips screw lock 1x LC/APC Duplex SM Adapter

Variant

Outdoor FTTx Enclosures

Width W (Imperial)

5.12

Width W (Metric)

130

Height H (Imperial)

10.35

Height H (Metric)	263
Depth D (imperial)	1.46
Depth D (metric)	37

Material	Acrylonitrile Butadiene Styrene, UV-stabilized (ABSUV)
-----------------	--

Material Shortcut ABS

Package Quantity(Imperial)	20
-----------------------------------	----

Package Quantity (Metric) 20

Customs Number	8536700000
-----------------------	------------