

## Specification Sheet

Part Number: CL-LM10C-01



Rapid installation requiring no specialized tools saves time and money. Highly repeatable – the quality of the seal is not dependent on the skill of the engineer. Tested beyond a 20-foot water head (58.8kPa), exhibiting excellent sealing properties.

Cablelok LM10C 2 x 4.0 - 6.5 mm x 1, CR, Black, 1/pkg

|                            |   |
|----------------------------|---|
| <b>Article Number</b>      | 857-50203   |
| <b>Type</b>                | CABLELOK-LM10C-01   |
| <b>Color</b>               | Black (BK)  |
| <b>Quantity Per</b>        | bag   |
| <b>Product Description</b> | HellermannTyton's patented Cablelok mechanical seal enables fast, safe cable installation, providing a repeatable and consistent seal between the cable and the closure port with excellent non-leak performance. Installation times are typically reduced by up to 90 percent. |
| <b>Short Description</b>   | Cablelok LM10C 2 x 4.0 - 6.5 mm x 1, CR, Black, 1/pkg   |
| <b>Global Part Name</b>    | CABLELOK-LM10C-01   |

|                                    |   |
|------------------------------------|---|
| <b>Technical Description</b>       | The LM Port Cablelok is a mechanical seal manufactured from Neoprene rubber, Minlon and Acetal. There are 5 Cablelok's which cover a cable range of 4.8mm – 15.0mm four of which have a dual outlet for loop through applications, the fifth being a port plug for blocking unused LM sized drop ports. |
| <b>Contents of pkg/kit</b>         | 1 X CABLELOK-LM10C, 1 x Allen Key, 2 x Lubricating Wipe   |
| <b>Port Count</b>                  | 2   |
| <b>Variant</b>                     | Oval - LM   |
| <b>Material</b>                    | Chloroprene Rubber (CR)   |
| <b>Material Shortcut</b>           | CR  |
| <b>Package Quantity (Imperial)</b> | 1   |
| <b>Package Quantity (Metric)</b>   | 1   |
| <b>Customs Number</b>              | 9030400000  |