

Specification Sheet

Part Number: CCP-SAP-W



Customer Connection Point, with SC-APC Simplex Adapter and 1 m SC-APC Pigtail, PC, White, 1/pkg

Article Number	904-01127
Type	CCP-SAP-W
Color	White (WH)
Features & Benefits	<ul style="list-style-type: none">•Fully water sealed, achieving an IP-68 (NEMA 6P) rating, for use in wall or handhole installations.•Separate inbound/outbound access points ensure cable sealing and segregation.•Single subscriber splice or patch to connect a home or outdoor device.
Quantity Per	EA

Product Description

The Customer Connection Point (CCP) is manufactured from UL 94 V-0 and UV stable black polycarbonate and has a fully detachable snap-on lid. The closure has 2 separate cable access points which are sealed with a silicon cable entry kit (cable diameter range 4.6 mm - 5.6 mm) to maintain the IP68 rating. A GORE-TEX breather membrane is fitted to the lid to prevent condensation forming in the base of the closure. The unit can be supplied with one SC Simplex or LC Duplex and matching pigtails and provides splice management for two heat shrink splices. Internal fiber management features ensure that a 30 mm minimum bend radius is maintained within the closure and provides fiber storage capacity for any excess fiber.

Short Description

Customer Connection Point, with SC-APC Simplex Adapter and 1 m SC-APC Pigtail, PC, White, 1/pkg

Global Part Name

CCP-SAP-W-PC-WH

Port Count

2

Variant

Outdoor Enclosure

Width W (Imperial)

3.5

Width W (Metric)

89.0

Height H (Imperial)

6.30

Height H (Metric)

160.0

Depth D (imperial)

1.10

Depth D (metric)

28.0

Material

Polycarbonate (PC)

Material Shortcut

PC

Package Quantity(Imperial)

1

Package Quantity (Metric)

1

Weight (Metric)

0.142

Weight (Imperial)

0.313