

## 105°C Super Vu-Tron® Supreme 300 and 600 Volt UL/CSA Portable Cord



\*Product images are for illustrative purposes only and may differ from the actual product.

### Category Conductor Description:

- 18 through 10 AWG fully annealed stranded tinned copper per ASTM B-174

### Category Jacket Description:

- Super Vu-Tron® Supreme, yellow Temperature Range: -50°C to +105°C UL/CSA Voltage Rating: 300 Volts Type SJOOW; 600 Volts Type SOOW

### Category Insulation Description:

- EPDM Premium-grade, color-coded, oil-resistant 105°C

### Applications:

- Machine tools
- Power tools
- Dockside power applications
- Motor leads
- Portable machinery
- Cranes
- Submersible pumps

### Standards:

- UL Flexible Cord – UL Subject 62
- CSA Flexible Cord – C22.2-49
- MSHA Approved
- RoHS Compliant
- OSHA Acceptable

Color Code Chart	
# of Conductors	Color
1	Black
2	White
3	Green
4	Red

5	Orange
6	Lt Blue
7	White/Black Stripe
8	Red/Black Stripe
9	Green/Black Stripe
10	Orange/Black Stripe
11	Light Blue/Black Stripe
12	Black/White Stripe
13	Red/White Stripe
14	Green/White Stripe
15	Light Blue/White Stripe
16	Black/Red Stripe
17	White/Red Stripe
18	Orange/Red Stripe
19	Light Blue/Red Stripe
20	Red/Green Stripe
21	Orange/Green Stripe
22	Black
23	White
24	Green
25	Red

Part Number Table

Part#	Gauge	Conductors	Stranding	Insulation Thickness	Outside Diameter Inches	Material Weight (Lbs./M')
B11203-V	12	3	168/34	.045"	.600"	224

\*Fittings are available for these products. Note: The data shown are approximate and subject to standard industry and manufacturer tolerances.  
\*Ampacities for portable cable, continuous duty (Ambient temperature of 40°C) May not be suitable for all installations per National Electric Code.

Selling Exclusively Through Distribution Since 1977 <sup>TM</sup> | phone: 800-292-OMNI | website: [omnicable.com](http://omnicable.com)  
Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •  
St. Louis • Tampa • Toronto  
© 2020 Omni Cable LLC