

105°C Super Vu-Tron® Supreme 300 and 600 Volt UL/CSA Portable Cord



*Product images are for illustrative purposes only and may differ from the actual product.

Category Conductor Description:

- 18 through 10 AWG fully annealed stranded tinned copper per ASTM B-174

Category Jacket Description:

- Super Vu-Tron® Supreme, yellow Temperature Range: -50°C to +105°C UL/CSA Voltage Rating: 300 Volts Type SJOOW; 600 Volts Type SOOW

Category Insulation Description:

- EPDM Premium-grade, color-coded, oil-resistant 105°C

Applications:

- Machine tools
- Power tools
- Dockside power applications
- Motor leads
- Portable machinery
- Cranes
- Submersible pumps

Standards:

- UL Flexible Cord – UL Subject 62
- CSA Flexible Cord – C22.2-49
- MSHA Approved
- RoHS Compliant
- OSHA Acceptable

Selling Exclusively Through Distribution Since 1977 TM | phone: 800-292-OMNI | website: omnicable.com

Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •

St. Louis • Tampa • Toronto

© 2020 Omni Cable LLC