

## 12 AWG – 19×25 Stranded Tinned Copper

Multiconductor - 600 Volt  
Overall Aluminum Shield  
Polyethylene Insulation



\*Product images are for illustrative purposes only and may differ from the actual product.

### Category Conductor Description:

- Stranded tinned copper

### Category Insulation Description:

- Polyethylene (PE)

### Shield:

- 100% aluminum/polyester with stranded tinned copper drain wire

### Category Jacket Description:

- Gray, Polyvinyl Chloride (PVC)

| Color Code Chart |       |
|------------------|-------|
| # of Pairs       | Color |
| 1                | Black |
| 2                | Clear |
| 3                | Red   |
| 4                | Green |

Part Number Table

| Part#  | Gauge | Pairs | Stranding | Insulation Thickness | Jacket Thickness | Outside Diameter Inches | Material Weight (Lbs./M') |
|--------|-------|-------|-----------|----------------------|------------------|-------------------------|---------------------------|
| D11202 | 12    | 1     | 19x25 TC  | 0.037                | 0.04             | 0.4                     | 101.1                     |

Note: The data shown is approximate and subject to standard industry and manufacturer tolerances.

Selling Exclusively Through Distribution Since 1977 <sup>TM</sup> | phone: 800-292-OMNI | website: [omnicable.com](http://omnicable.com)  
Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •  
St. Louis • Tampa • Toronto  
© 2020 Omni Cable LLC