

12 AWG – 19x25 Stranded Tinned Copper

Multiconductor - 600 Volt
Overall Aluminum Shield
Polyethylene Insulation



*Product images are for illustrative purposes only and may differ from the actual product.

Category Conductor Description:

- Stranded tinned copper

Category Insulation Description:

- Polyethylene (PE)

Shield:

- 100% aluminum/polyester with stranded tinned copper drain wire

Category Jacket Description:

- Gray, Polyvinyl Chloride (PVC)

Color Code Chart	
# of Pairs	Color
1	Black
2	Clear
3	Red
4	Green

Part Number Table

Part#	Gauge	Pairs	Stranding	Insulation Thickness	Jacket Thickness	Outside Diameter Inches	Material Weight (Lbs./M')
D11202	12	1	19x25 TC	0.037	0.04	0.4	101.1

Note: The data shown is approximate and subject to standard industry and manufacturer tolerances.

Selling Exclusively Through Distribution Since 1977 TM | phone: 800-292-OMNI | website: omnicable.com
Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •
St. Louis • Tampa • Toronto
© 2020 Omni Cable LLC