

12 AWG - 19x25 Stranded Tinned Copper

**Multiconductor - 600 Volt
Overall Aluminum Shield
Polyethylene Insulation**

Security and Alarm Cable

Image Coming Soon

Category Conductor Description:

- Stranded tinned copper

Category Insulation Description:

- Polyethylene (PE)

Shield:

- 100% aluminum/polyester with stranded tinned copper drain wire

Category Jacket Description:

- Gray, Polyvinyl Chloride (PVC)

Applications:

- Paired cables allow balanced signal transmission which results in lower crosstalk through common mode rejection
- Due to the improved noise immunity of twisted pairs, they generally permit higher data speeds than multi-conductor cables

Standards:

- CEC CM CL2
- CEC CM
- 600 Volt Rated
- 80°C rated

PART NUMBER TABLE

Part#	Gauge	Pairs	Stranding	Insulation Thickness	Jacket Thickness	Outside Diameter Inches	Material Weight (Lbs./M')
D11202	12	1	19x25 TC	0.037	0.04	0.4	101.1

Note: The data shown are approximate and subject to standard industry and manufacturer tolerances.

Selling Exclusively Through Distribution Since 1977™ | phone: 800-292-OMNI | website: omnicable.com
Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco •
Seattle • St. Louis • Tampa • Toronto
© 2020 Omni Cable LLC