

## 12 CHANNEL DX-Series Distribution – Riser Rated Cables

### Fiber:

---

- SLX, Low Water Peak, Single-Mode ITU-T G.652.D

### Category Description:

---

- Indoor/Outdoor tightbuffered fiber optic cable

### Unit Of Measure:

---

- per 1000 ft

### Standards:

---

- UL 1651
- UL 1666
- GR-409-CORE
- ICEA-S-104-696
- ICEA-S-83-596
- TIA-568
- TIA-598
- UL-listed type OFNR in accordance with
- NEC sections 770-179 (B) and 770-154 (B)

### Category Jacket Description:

---

- PVC for 4- to 24-fiber counts. For all other fiber counts, please contact OCC Sales.

### Category Standards:

---

- UL 1651 UL 1666 GR-409-CORE ICEA-S-104-696 ICEA-S-83-596 TIA-568 TIA-598 UL-listed type OFNR in accordance with NEC sections 770-179 (B) and 770-154 (B) for use in vertical runs in building riser shafts or from floor to floor. Meets or exceeds requirements for intra-building fiber optic cables as outlined in GR-409-CORE.

### Applications:

---

- Indoor/Outdoor tight-bound tight-buffered design allows cables to be installed in intra-building backbone and inter-building campus locations without costly transitions between cable types
- Ideal configuration for a single termination point requiring multiple fibers

- for use in vertical runs in building riser shafts
- or from floor to floor. Meets or exceeds
- requirements for intra-building fiber optic
- cables as outlined in GR-409-CORE.

Part Number Table

Part#	Fiber Count	Material Weight (Lbs./M')	Max Tensile Load In Service
DX048DSLX9KR	48	63	310
DX012DSLX9KR	12	25	135

Selling Exclusively Through Distribution Since 1977 <sup>TM</sup> | phone: 800-292-OMNI | website: [omnicable.com](http://omnicable.com)

Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •

St. Louis • Tampa • Toronto

© 2020 Omni Cable LLC