

14 AWG – 19×27 Stranded Tinned Copper

Multi-Conductor
Unshielded - 300 Volt / 600 Volt
PVC Insulation - 80°C

Category Conductor Description:

- Stranded tinned copper multi-conductors 2 & 3 conductors - 300 Volt 4+ conductors - 600 Volt

Category Jacket Description:

- Gray, Polyvinyl Chloride (PVC) over cabled conductors

Standards:

- UL Rated - 80°C
- NEC CL3, Passes VW-1 vertical wire flame test
- Suggest Working Voltage: 600 Volt

Category Insulation Description:

- Polyvinyl Chloride (PVC)

Applications:

- Applications include computers, communications, instrumentation, sound, control, audio, and data transmission
- Designed to protect signal integrity under critical conditions by reducing hum, noise, and crosstalk

Part Number Table

Part#	Gauge	Conductors	Stranding	Insulation Thickness	Jacket Thickness	Outside Diameter Inches	Material Weight (Lbs./M')
D91404	14	4	19x27 TC	0.045	0.045	0.486	149
D91405	14	5	19x27 TC	0.045	0.06	0.573	197
D91407	14	7	19x27 TC	0.045	0.06	0.623	257
D91412	14	12	19x27 TC	0.045	0.065	0.824	460

Note: The data shown is approximate and subject to standard industry and manufacturer tolerances.

Selling Exclusively Through Distribution Since 1977 TM | phone: 800-292-OMNI | website: omnicable.com

Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •

St. Louis • Tampa • Toronto

© 2020 Omni Cable LLC