

14 AWG – 42×30 Stranded Tinned Copper

Paired - Unshielded
Stranded Conductor
PVC Insulation - 300 Volt

Category Conductor Description:

- Tinned Copper 300 Volt

Category Insulation Description:

- Polyvinyl Chloride (PVC)

Category Jacket Description:

- Gray, Polyvinyl Chloride (PVC)

Applications:

- Allow balanced signal transmission which results in lower crosstalk through common mode rejection
- Permits higher data speeds than multi-conductor cables

Standards:

- UL Listed: 90°C
- Voltage: 300 Volt rating

| Color Code Chart | |
|------------------|-------|
| # of Pairs | Color |
| 1 | Black |
| 2 | White |

Part Number Table

| Part# | Gauge | Pairs | Stranding | Insulation Thickness | Jacket Thickness | Outside Diameter Inches | Material Weight (Lbs./M') |
|--------|-------|-------|-----------|----------------------|------------------|-------------------------|---------------------------|
| D91402 | 14 | 1 | 42x30 TC | 0.031 | 0.032 | 0.34 | 58 |

Note: The data shown is approximate and subject to standard industry and manufacturer tolerances.

Selling Exclusively Through Distribution Since 1977 TM | phone: 800-292-OMNI | website: omnicable.com
Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •
St. Louis • Tampa • Toronto
© 2020 Omni Cable LLC