

15kV – URD Cable, EPR, 133% Insulation

EPR Insulation - LDPE Jacket
MV-90 - 133% Insulation Level
15kV - Single Conductor



*Product images are for illustrative purposes only and may differ from the actual product.

Category Conductor Description:

- Soft-annealed copper Class B stranding

Category Insulation Description:

- Thermoset Ethylene Propylene Rubber (EPR)

Concentric Neutral:

- Soft-annealed solid copper wires

Applications:

- Underground primary cable for residential and commercial distribution circuits
- Suitable for use in wet or dry locations, installed in underground ducts or direct buried
- Wet and dry locations: Normal 105°C, Emergency 140°C, Short Circuit 250°C

Conductor Shield:

- Semi-conducting Cross-Linked Polyethylene (XLPE)

Insulation Shield:

- Semi-conducting Cross-Linked Polyethylene (XLPE)

Category Jacket Description:

- Black, sunlight resistant, linear low density Polyethylene (LDPE) encapsulating the neutral wires Outer jacket has three extruded red stripes for identification purposes

Standards:

- AEIC CS8
- ICEA S-94-649; T-31-610; T-34-664

Part Number Table

Part#	Gauge	Stranding	Nominal OD over Insulation	Nominal OD over Jacket	Nominal OD Overall	Material Weight (Lbs./M')
MU30201C	2	7	.77	.050	1.08	789
MU31/001C	1/0	19	.85	.050	1.20	1095
MU32/001C	2/0	19	.90	.050	1.28	1327
MU34/001C	4/0	19	1.01	.050	1.41	1874
MU325001C	250	37	1.06	.050	1.39	1623
MU335001C	350	37	1.16	.050	1.52	2132
MU350001C	500	37	1.29	.080	1.76	2976

Note: The data shown are approximate and subject to standard industry and manufacturer tolerances

Selling Exclusively Through Distribution Since 1977 [™] | phone: 800-292-OMNI | website: omnicable.com
 Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •
 St. Louis • Tampa • Toronto
 © 2020 Omni Cable LLC