

15kV - URD - XLP Insulation

TR-XLPE Insulation - LDPE Jacket
15kV - URD



*Product images are for illustrative purposes only and may differ from the actual product.

Category Conductor Description:

- Compressed Class B, 7 strand aluminum or copper A for aluminum C for copper

Category Insulation Description:

- Extruded tree-retardant cross-linked Polyethylene (XLPE)

Concentric Neutral:

- Bare copper concentric neutral wires with water-swellable powder and ripcords

Standards:

- ICEA S-94-649
- AEIC CS8
- PECO spec 125-P-18

Conductor Shield:

- Extruded semi-conducting thermoset polymer

Insulation Shield:

- Extruded semiconducting thermoset polymer

Outer Jacket:

- Black linear low-density Polyethylene (LDPE) with three longitudinal red stripes

Part Number Table

Part#	Gauge	Conductors	Stranding	Insulation Thickness	Neutral AWG	Nominal OD over Insulation	Outside Diameter Inches	Material Weight (Lbs./M')
MUP10201-A	2		7	0.175	10X14	.752	0.99	482
MUP10201-C	2	Copper	7	0.175	16X14	.700	0.99	698

Note: The data shown are approximate and subject to standard industry and manufacturer tolerances

Selling Exclusively Through Distribution Since 1977 TM | phone: 800-292-OMNI | website: omnicable.com

Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •
St. Louis • Tampa • Toronto

© 2020 Omni Cable LLC