

## 15kV - URD - XLP Insulation

TR-XLPE Insulation - LDPE Jacket  
15kV - URD



\*Product images are for illustrative purposes only and may differ from the actual product.

### Category Conductor Description:

---

- Compressed Class B, 7 strand aluminum or copper A for aluminum C for copper

### Category Insulation Description:

---

- Extruded tree-retardant cross-linked Polyethylene (XLPE)

### Concentric Neutral:

---

- Bare copper concentric neutral wires with water-swellable powder and ripcords

### Standards:

---

- ICEA S-94-649
- AEIC CS8
- PECO spec 125-P-18

### Conductor Shield:

---

- Extruded semi-conducting thermoset polymer

### Insulation Shield:

---

- Extruded semiconducting thermoset polymer

### Outer Jacket:

---

- Black linear low-density Polyethylene (LDPE) with three longitudinal red stripes

## Part Number Table

Part#	Gauge	Conductors	Stranding	Insulation Thickness	Neutral AWG	Nominal OD over Insulation	Outside Diameter Inches	Material Weight (Lbs./M')
MUP10201-A	2		7	0.175	10X14	.752	0.99	482
MUP10201-C	2	Copper	7	0.175	16X14	.700	0.99	698

Note: The data shown are approximate and subject to standard industry and manufacturer tolerances

Selling Exclusively Through Distribution Since 1977 <sup>TM</sup> | phone: 800-292-OMNI | website: [omnicable.com](http://omnicable.com)

Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •  
St. Louis • Tampa • Toronto

© 2020 Omni Cable LLC