

15kv URD

TR-XLP Insulation - LDPE Jacket
Full Neutral - Copper Conductor
15kV - URD - 133% Insulation Level

Medium Voltage



*Product images are for illustrative purposes only and may differ from the actual product.

Category Conductor Description:

- Soft-annealed uncoated copper compressed class B stranding

Conductor Shield:

- Semi-conducting Cross-linked Polyethylene (XLPE)

Category Insulation Description:

- Tree-retardant cross-linked Polyethylene (TR-XLPE)

Insulation Shield:

- Semi-conducting Cross-linked Polyethylene (XLPE)

Category Jacket Description:

- Black sunlight resistant low density Polyethylene (LDPE) encapsulating the neutral wires The outer jacket shall have three extruded red stripes (120 degrees apart) for identification

Applications:

- For use in underground residential distribution, as primary power cable in direct buried or underground in duct

Standards:

- ICEA S-94-649
- AEIC CS12

PART NUMBER TABLE						
Part#	Gauge	Stranding	Insulation Thickness	Neutral AWG	Outside Diameter Inches	Material Weight (Lbs./M')
MVX30201C	2	7	220 mils	16x14	1.07	751
MVX30101C	1	19	220 mils	13x12	1.14	904
MVX31/001C	1/0	19	220 mils	16x12	1.18	1051
MVX32/001C	2/0	19	220 mils	13X10	1.27	1284
MVX33/001C	3/0	19	220 mils	16X10	1.32	1512
MVX34/001C	4/0	19	220 mils	16X9	1.4	1830

Note: The data shown are approximate and subject to standard industry and manufacturer tolerances.

Selling Exclusively Through Distribution Since 1977™ | phone: 800-292-OMNI | website: omnicable.com
Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco •
Seattle • St. Louis • Tampa • Toronto
© 2020 Omni Cable LLC