

## 16 AWG – 19x29 Stranded Tinned Copper

**Multi-Conductor - 80°C**  
**Unshielded - 300 Volt / 600 Volt**  
**PVC Insulation - PVC Jacket**

**Security and Alarm Cable**

Image Coming Soon

### Category Conductor Description:

---

- Tinned Copper 2 & 3 conductors - 300 Volt 4+ conductors - 600 Volt

### Category Insulation Description:

---

- Polyvinyl Chloride (PVC)

### Category Jacket Description:

---

- Gray, Polyvinyl Chloride (PVC) over cabled conductors

### Applications:

---

- Used for computers, communications, instrumentation, sound, control, audio, and data transmissions
- Designed to protect signal integrity under critical conditions by reducing noise

### Standards:

---

- UL Rated - 80°C
- Suggested Working Voltage: 600 Volt

**PART NUMBER TABLE**

<b>Part#</b>	<b>Gauge</b>	<b>Conductors</b>	<b>Stranding</b>	<b>Insulation Thickness</b>	<b>Jacket Thickness</b>	<b>Outside Diameter Inches</b>	<b>Material Weight (Lbs./M')</b>
D91602	16	2	19x29 TC	0.023	0.032	0.266	39
D91603	16	3	19x29 TC	0.023	0.032	0.283	52.4
D91604	16	4	19x29 TC	0.031	0.045	0.382	88
D91605	16	5	19x29 TC	0.031	0.045	0.417	109
D91607	16	7	19x29 TC	0.031	0.045	0.458	143
D91608	16	8	19x29 TC	0.031	0.045	0.496	170
D91609	16	9	19x29 TC	0.031	0.045	0.533	177
D91612	16	12	19x29 TC	0.031	0.06	0.627	251
D91615	16	15	19x29 TC	0.031	0.06	0.694	307
D91619	16	19	19x29 TC	0.031	0.065	0.74	363
D91625	16	25	19x29 TC	0.031	0.065	0.879	485

Note: The data shown are approximate and subject to standard industry and manufacturer tolerances.

**Selling Exclusively Through Distribution Since 1977™ | phone: 800-292-OMNI | website: [omnicable.com](http://omnicable.com)**  
**Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco •**  
**Seattle • St. Louis • Tampa • Toronto**  
**© 2020 Omni Cable LLC**