

16 AWG- 19x29 Stranded Tinned Copper - 1 pair

Multiconductor - 600 Volt
Overall Aluminum Shield
Polyethylene Insulation



*Product images are for illustrative purposes only and may differ from the actual product.

Category Conductor Description:

- Stranded tinned copper

Shield:

- 100% aluminum/polyester with stranded tinned copper drain wire

Applications:

- Paired cables allow balanced signal transmission which results in lower crosstalk through common mode rejection
- Due to the improved noise immunity of twisted pairs, they generally permit higher data speeds than multi-conductor cables

Category Insulation Description:

- Polyethylene (PE), twisted pair

Category Jacket Description:

- Gray, Polyvinyl Chloride (PVC)

Standards:

- CEC CM CL2 CEC CM 600 Volt Rated (UL AWM type 20253)
300 Volt Rated (UL type CM) 80°C rated

Color Code Chart	
# of Pairs	Color
1	Black
2	Clear
3	Red
4	Green

Part Number Table

Part#	Gauge	Pairs	Stranding	Insulation Thickness	Jacket Thickness	Outside Diameter Inches	Material Weight (Lbs./M')
D11602	16	1	19x29 TC	0.032	0.032	0.312	42

Note: The data shown is approximate and subject to standard industry and manufacturer tolerances

Selling Exclusively Through Distribution Since 1977 TM | phone: 800-292-OMNI | website: omnicable.com
Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •
St. Louis • Tampa • Toronto
© 2020 Omni Cable LLC