

16 AWG- 19x29 Stranded Tinned Copper - 1 pair

**Multiconductor - 600 Volt**  
**Overall Aluminum Shield**  
**Polyethylene Insulation**

Montrose



\*Product images are for illustrative purposes only and may differ from the actual product.

**Category Conductor Description:**

- Stranded tinned copper

**Category Insulation Description:**

- Polyethylene (PE), twisted pair

**Shield:**

- 100% aluminum/polyester with stranded tinned copper drain wire

**Category Jacket Description:**

- Gray, Polyvinyl Chloride (PVC)

**Applications:**

- Paired cables allow balanced signal transmission which results in lower crosstalk through common mode rejection
- Due to the improved noise immunity of twisted pairs, they generally permit higher data speeds than multi-conductor cables

**Standards:**

- CEC CM CL2 CEC CM 600 Volt Rated (UL AWM type 20253)  
300 Volt Rated (UL type CM) 80°C rated

Color Code Chart	
# of Pairs	Color
1	Black
2	Clear
3	Red
4	Green

**PART NUMBER TABLE**

Part#	Gauge	Pairs	Stranding	Insulation Thickness	Jacket Thickness	Outside Diameter Inches	Material Weight (Lbs./M')
D11602	16	1	19x29 TC	0.032	0.032	0.312	42

Note: The data shown are approximate and subject to standard industry and manufacturer tolerances.

**Selling Exclusively Through Distribution Since 1977™ | phone: 800-292-OMNI | website: [omnicable.com](http://omnicable.com)**  
**Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco •**  
**Seattle • St. Louis • Tampa • Toronto**  
**© 2020 Omni Cable LLC**