

## 16 AWG - 19x29 Stranded Tinned Copper - 3 conductor

Multiconductor - 300 Volt  
Overall Aluminum Shield  
Polyethylene Insulation



\*Product images are for illustrative purposes only and may differ from the actual product.

### Category Conductor Description:

- Stranded tinned copper

### Shield:

- 100% aluminum/polyester with stranded tinned copper drain wire

### Applications:

- Paired cables allow balanced signal transmission which results in lower crosstalk through common mode rejection
- Due to the improved noise immunity of twisted pairs, they generally permit higher data speeds than multi-conductor cables

### Category Insulation Description:

- Polyethylene (PE), twisted pair

### Category Jacket Description:

- Gray, Polyvinyl Chloride (PVC)

### Standards:

- CEC CM CL2
- CEC CM
- 300 Volt Rated (AWM 2107 at 600V)
- 80°C rated

Color Code Chart	
# of Conductors	Color
1	Black
2	Clear
3	Red
4	Green

Part Number Table

Part#	Gauge	Conductors	Stranding	Insulation Thickness	Jacket Thickness	Outside Diameter Inches	Material Weight (Lbs./M')
D11603	16	3	19x29 TC	0.031	0.031	0.33	59

Note: The data shown is approximate and subject to standard industry and manufacturer tolerances.

Selling Exclusively Through Distribution Since 1977 <sup>TM</sup> | phone: 800-292-OMNI | website: [omnicable.com](http://omnicable.com)  
Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •  
St. Louis • Tampa • Toronto  
© 2020 Omni Cable LLC