

18 AWG – 16×30 Stranded Tinned Copper – Multi-Conductor

Multi-Conductor - 300 Volt
Overall Braid Shield - 75°C
PVC Insulation

Security and Alarm Cable

Image Coming Soon

Category Conductor Description:

- Stranded tinned copper

Category Insulation Description:

- Polyvinyl Chloride (PVC)

Shield:

- Tinned copper braid shield, 75% shield coverage

Category Jacket Description:

- Gray, Polyvinyl Chloride (PVC)

Applications:

- Used for computers, communications, instrumentation, sound, control, audio, and data transmissions
- Designed to protect signal integrity under critical conditions by reducing noise

Standards:

- NEC Article 800
- UL 444
- UL 758
- AWM Style 2095
- 75°C

PART NUMBER TABLE

Part#	Gauge	Conductors	Stranding	Insulation Thickness	Jacket Thickness	Outside Diameter Inches	Material Weight (Lbs./M')
D111802	18	2	16x30 TC	0.016	0.032	0.252	19
D111803	18	3	16x30 TC	0.016	0.032	0.264	25
D111804	18	4	16x30 TC	0.016	0.032	0.286	31

Note: The data shown are approximate and subject to standard industry and manufacturer tolerances.

Selling Exclusively Through Distribution Since 1977™ | phone: 800-292-OMNI | website: omnicable.com
Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco •
Seattle • St. Louis • Tampa • Toronto
© 2020 Omni Cable LLC