

## 18 AWG – 16x30 Stranded Tinned Copper - Shielded

**Multi-Conductor - 300 Volt**  
**Overall Aluminum Shield**  
**S-R PVC Insulation - 60°C**

**Security and Alarm Cable**

Image Coming Soon

### Category Conductor Description:

---

- Tinned copper

### Category Insulation Description:

---

- Semi-rigid Polyvinyl Chloride (S-R PVC)

### Shield Drain:

---

- Aluminum-polyester shield Tinned copper drain wire with 100% shield coverage

### Category Jacket Description:

---

- Gray, Polyvinyl Chloride (PVC)

### Applications:

---

- Used for computers, communications, instrumentation, sound, control, audio, and data transmissions
- Designed to protect signal integrity under critical conditions by reducing noise

### Standards:

---

- UL Rated: 60°C, UL AWM Style 2598
- Voltage: UL 300 Volt

**PART NUMBER TABLE**

<b>Part#</b>	<b>Gauge</b>	<b>Conductors</b>	<b>Stranding</b>	<b>Insulation Thickness</b>	<b>Jacket Thickness</b>	<b>Outside Diameter Inches</b>	<b>Material Weight (Lbs./M')</b>
D21806	18	6	16x30 TC	0.017	0.032	0.297	67.1
D21808	18	8	16x30 TC	0.017	0.032	0.339	84.7
D21810	18	10	16x30 TC	0.017	0.032	0.362	100.7
D21812	18	12	16x30 TC	0.017	0.032	0.394	119.4
D21815	18	15	16x30 TC	0.017	0.045	0.442	145
D21820	18	20	16x30 TC	0.017	0.045	0.496	189.3
D21825	18	25	16x30 TC	0.017	0.045	0.598	243

Note: The data shown are approximate and subject to standard industry and manufacturer tolerances.

Selling Exclusively Through Distribution Since 1977™ | phone: 800-292-OMNI | website: [omnicable.com](http://omnicable.com)  
Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco •  
Seattle • St. Louis • Tampa • Toronto  
© 2020 Omni Cable LLC