

18 AWG - 19x30 Stranded Tinned Copper - 4 conductor

Multi-Conductor - 300 Volt
Overall Aluminum Shield
S-R PVC Insulation - 75°C



*Product images are for illustrative purposes only and may differ from the actual product.

Category Conductor Description:

- Tinned copper

Category Insulation Description:

- Semi-Rigid Polyvinyl Chloride (SR-PVC), conductors cabled

Shield Drain:

- Aluminum-polyester shield Tinned copper drain wire with 100% shield coverage

Category Jacket Description:

- Gray, Polyvinyl Chloride (PVC)

Applications:

- Used for computers, communications, instrumentation, sound, control, audio, and data transmissions
- Designed to protect signal integrity under critical conditions by reducing noise

Standards:

- UL Rated - 75°C
- Voltage: UL 300 Volt

Color Code Chart	
# of Conductors	Color
1	Black
2	Red
3	White
4	Green
5	Brown
6	Blue
7	Orange
8	Yellow
9	Purple

10	Gray
11	Pink
12	Tan
13	Red/Black Stripe
14	White/Black Stripe
15	Green/Black Stripe
16	Blue/Black Stripe
17	Orange/Black Stripe
18	Yellow/Black Stripe
19	Purple/Black Stripe
20	Gray/Black Stripe
21	Pink/Black Stripe
22	Tan/Black Stripe
23	Black/White Stripe
24	Red/White Stripe
25	Green/White Stripe
26	Blue/White Stripe
27	Brown/White Stripe
28	Orange/White Stripe
29	Yellow/White Stripe
30	Purple/White Stripe

Part Number Table

Part#	Gauge	Conductors	Stranding	Insulation Thickness	Jacket Thickness	Outside Diameter Inches	Material Weight (Lbs./M')
D21804	18	4	19x30 TC	0.01	0.035	0.227	39

Note: The data shown is approximate and subject to standard industry and manufacturer tolerances

Selling Exclusively Through Distribution Since 1977 TM | phone: 800-292-OMNI | website: omnicable.com
Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •
St. Louis • Tampa • Toronto
© 2020 Omni Cable LLC