

18 AWG – Multi-Conductor – Plenum Jacket

Multi-Pair
Overall Aluminum/Polyester Shield
Drain Wire
Plenum



*Product images are for illustrative purposes only and may differ from the actual product.

Category Conductor Description:

- Twisted pairs with overall foil shield

Shield Drain:

- Overall aluminum/polyester foil shield with 100% coverage

Applications:

- Signal and control applications

Category Insulation Description:

- Low smoke Polyvinyl Chloride (PVC)

Category Jacket Description:

- Plenum, low smoke Polyvinyl Chloride (PVC)

Standards:

- CMP/CL3P

Part Number Table

| Part# | Gauge | Pairs | Stranding | Insulation Thickness | Jacket Thickness | Outside Diameter Inches | Material Weight (Lbs./M') |
|---------|-------|-------|-----------|----------------------|------------------|-------------------------|---------------------------|
| G131802 | 18 | 2 | 7x26 | 0.009 | 0.014 | 0.183 | 33.6 |
| G131803 | 18 | 3 | 7x26 | 0.009 | 0.014 | 0.267 | 49.7 |

Note: The data shown is approximate and subject to standard industry and manufacturer tolerances

Selling Exclusively Through Distribution Since 1977 TM | phone: 800-292-OMNI | website: omnicable.com

Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •
St. Louis • Tampa • Toronto

© 2020 Omni Cable LLC