

18 AWG – Multi-Pair – Plenum Jacket

Individually Shielded Pairs
 Aluminum/Mylar Shield
 Plenum Rated
 Plenum



*Product images are for illustrative purposes only and may differ from the actual product.

Category Conductor Description:

- Stranded bare copper

Shield Drain:

- Aluminum/Mylar shielded pairs with one drain wire per pair

Applications:

- Signal and control applications

Category Insulation Description:

- Low smoke Polyvinyl Chloride (PVC)

Category Jacket Description:

- Plenum, low smoke Polyvinyl Chloride (PVC)

Standards:

- CMP/CL3P

Color Code Chart	
# of Pairs	Color
1	Black & Red
2	Black & White
3	Black & Green
4	Black & Blue
5	Black & Yellow
6	Black & Brown
7	Black & Orange
8	Red & White
9	Red & Green
10	Red & Blue
11	Red & Yellow
12	Red & Brown

13	Red & Orange
14	Green & White
15	Green & Blue
16	Green & Yellow
17	Green & Brown
18	Green & Orange
19	White & Blue
20	White & Yellow

Part Number Table

Part#	Gauge	Pairs	Stranding	Insulation Thickness	Jacket Thickness	Outside Diameter Inches	Material Weight (Lbs./M')
G151802	18	2	7x26	0.009	0.014	0.186	37.7
G151803	18	3	7x26	0.009	0.014	0.264	66

Note: The data shown is approximate and subject to standard industry and manufacturer tolerances

Selling Exclusively Through Distribution Since 1977 TM | phone: 800-292-OMNI | website: omnicable.com

Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •
St. Louis • Tampa • Toronto

© 2020 Omni Cable LLC