

**20 AWG – 7x28 Stranded Tinned Copper – 3 conductors**

**Multi-Conductor; 300 Volt  
Aluminum Shield; 60°C  
Polyethylene Insulation**

**Montrose**



\*Product images are for illustrative purposes only and may differ from the actual product.

**Category Conductor Description:**

- Tinned copper

**Category Insulation Description:**

- Polyethylene (PE), twisted pair

**Shield Drain:**

- Aluminum-polyester shield Tinned copper drain wire with 100% shield coverage

**Category Jacket Description:**

- Gray, Polyvinyl Chloride (PVC)

**Applications:**

- Used for computers, communications, instrumentation, sound, control, audio, and data transmissions
- Designed to protect signal integrity under critical conditions by reducing noise

**Standards:**

- UL Rated 60°C Voltage: UL 300 Volt

**PART NUMBER TABLE**

Part#	Gauge	Conductors	Stranding	Insulation Thickness	Jacket Thickness	Outside Diameter Inches	Material Weight (Lbs./M')
D12003	20	3	7x28 TC	0.016	0.033	0.21	25

Note: The data shown are approximate and subject to standard industry and manufacturer tolerances.

**Selling Exclusively Through Distribution Since 1977™ | phone: 800-292-OMNI | website: [omnicable.com](http://omnicable.com)**  
**Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco •**  
**Seattle • St. Louis • Tampa • Toronto**  
**© 2020 Omni Cable LLC**