

## 22 AWG – 7×30 Stranded Tinned Copper – Polypropylene - Shielded Pairs

Individual Shielded Pairs  
Polypropylene Insulation  
300 Volt - 80°C

### Category Conductor Description:

---

- Stranded tinned copper

### Shield:

---

- Each pair shielded with 100% aluminum foil/polyester and 22 AWG stranded tinned copper drain wire \* Please note D32202, is two pair, each pair has aluminum/polyester shield The cable has one 24 AWG stranded tinned copper drain wire

### Applications:

---

- Paired cables allow balanced signal transmission which result in lower crosstalk through common mode rejection
- Due to the improved noise immunity of twisted pairs, they generally permit higher data speeds than multiconductors

### Category Insulation Description:

---

- Polypropylene (PP)

### Category Jacket Description:

---

- Gray, Polyvinyl Chloride (PVC)

### Standards:

---

- UL AWM 2919
- NEC type CM

**Part Number Table**

<b>Part#</b>	<b>Gauge</b>	<b>Pairs</b>	<b>Stranding</b>	<b>Outside Diameter Inches</b>	<b>Nominal Capacitance A</b>	<b>Nominal Capacitance B</b>	<b>Material Weight (Lbs./M')</b>
D32202	22	2	7x30 TC	0.16	35	55	17
D32203	22	3	7x30 TC	0.27	30	35	35
D32204	22	4	7x30 TC	0.252	30	35	41.6
D32206	22	6	7x30 TC	0.362	30	55	82.9
D32209	22	9	7x30 TC	0.417	30	55	117
D32211	22	11	7x30 TC	0.464	30	55	133
D32212	22	12	7x30 TC	0.464	30	55	152
D32215	22	15	7x30 TC	0.548	30	55	192
D32217	22	17	7x30 TC	0.577	30	55	215
D32219	22	19	7x30 TC	0.603	30	55	244
D32227	22	27	7x30 TC	0.709	30	55	346
D32237	22	37	7x30 TC	0.8	30	55	481

\* Capacitance between conductors \*\* Capacitance between one conductor and other conductors connected to shield

Selling Exclusively Through Distribution Since 1977 <sup>TM</sup> | phone: 800-292-OMNI | website: [omnicable.com](http://omnicable.com)

Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •  
St. Louis • Tampa • Toronto

© 2020 Omni Cable LLC