

## 22 AWG – 7×32 Stranded Tinned Copper

Stranded Multi-Conductor  
Overall Aluminum Shield  
S-R PVC Insulation - 300 Volt



\*Product images are for illustrative purposes only and may differ from the actual product.

### Category Conductor Description:

---

- Stranded tinned copper multi-conductors

### Shield:

---

- Aluminum polyester shield with stranded tinned copper drain wire

### Standards:

---

- UL 758
- UL 444
- NEC Article 800
- UL Listed CM
- UL Recognized AWM Style 2464 80°C 300 Volts
- cUL Listed Type CMG
- California State Fire Marshal Approved

### Category Insulation Description:

---

- Semi-rigid Polyvinyl Chloride (S-R PVC)

### Category Jacket Description:

---

- Gray, Polyvinyl Chloride (PVC)

**Part Number Table**

<b>Part#</b>	<b>Houston Wire &amp; Cable</b>	<b>Gauge</b>	<b>Conductors</b>	<b>Stranding</b>	<b>Insulation Thickness</b>	<b>Jacket Thickness</b>	<b>Outside Diameter Inches</b>	<b>Material Weight (Lbs./M')</b>
D22204	22-04SCMR	22	4	7x32	0.01	0.032	0.19	26.3
D22206	22-06SCMR	22	6	7x32	0.01	0.032	0.219	35.3
D22208	22-08SCMR	22	8	7x32	0.01	0.032	0.235	43
D22210		22	10	7x32	0.01	0.032	0.269	51.1
D22212	HW40002212	22	12	7x32	0.01	0.032	0.259	54.2
D22215		22	15	7x32	0.01	0.035	0.298	69.4
D22220		22	20	7x32	0.01	0.035	0.332	87.5
D22225		22	25	7x32	0.01	0.035	0.358	101

Note: The data shown is approximate and subject to standard industry and manufacturer tolerances Color Code: Vendor specific, please refer to vendor spec

**Selling Exclusively Through Distribution Since 1977™ | phone: 800-292-OMNI | website: [omnicable.com](http://omnicable.com)**  
**Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •**  
**St. Louis • Tampa • Toronto**  
 © 2020 Omni Cable LLC