

22 AWG - 7x28 Stranded Tinned Copper - 300V

Paired - Unshielded
Stranded Conductors - 80°C
PVC Insulation - 300 Volt

Category Conductor Description:

- Stranded tinned copper

Category Jacket Description:

- Gray, Polyvinyl Chloride (PVC)

Standards:

- NEC CMG
- CEC CMG
- Voltage: 300 Volt

Category Insulation Description:

- Polyvinyl Chloride (PVC), twisted pairs

Applications:

- Paired cables allow balanced signal transmission which results in lower crosstalk through common mode rejection
- The twisted pairs generally permit higher data speeds than multi-conductor cables

Part Number Table

Part#	Gauge	Pairs	Stranding	Insulation Thickness	Jacket Thickness	Outside Diameter Inches	Material Weight (Lbs./M')
D942001	20	1	7x28 TC	0.013	0.025	0.16	13
D942003	20	3	7x28 TC	0.013	0.035	0.299	50
D942006	20	6	7x28 TC	0.013	0.035	0.366	89
D942009	20	9	7x28 TC	0.013	0.035	0.429	125
D942015	20	15	7x28 TC	0.013	0.04	0.549	194

Note: The data shown is approximate and subject to standard industry and manufacturer tolerances

Selling Exclusively Through Distribution Since 1977 TM | phone: 800-292-OMNI | website: omnicable.com
 Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •
 St. Louis • Tampa • Toronto
 © 2020 Omni Cable LLC