

## 22 AWG - 7x30 Stranded Tinned Copper - Polyethylene

**Montrose**

Image Coming Soon

### Category Conductor Description:

---

- Tinned copper

### Category Insulation Description:

---

- Polyethylene (PE), conductors cabled

### Shield Drain:

---

- Aluminum-polyester shield Tinned copper drain wire with 100% shield coverage

### Category Jacket Description:

---

- Gray, Polyvinyl Chloride (PVC)

### Applications:

---

- Used for computers, communications, instrumentation, sound, control, audio, and data transmissions
- Designed to protect signal integrity under critical conditions by reducing noise

### Standards:

---

- CEC CM
- NEC CM
- Working Voltage: 300 Volt

## PART NUMBER TABLE

Part#	Gauge	Conductors	Stranding	Insulation Thickness	Jacket Thickness	Outside Diameter Inches	Material Weight (Lbs./M')
D12203	22	3	7x30 TC	0.016	0.033	0.196	20

Note: The data shown are approximate and subject to standard industry and manufacturer tolerances.

Selling Exclusively Through Distribution Since 1977™ | phone: 800-292-OMNI | website: [omnicable.com](http://omnicable.com)  
Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco •  
Seattle • St. Louis • Tampa • Toronto  
© 2020 Omni Cable LLC