

## 22 AWG - Multi-Pair - Omniplen Jacket

Multi-Pair  
Overall Aluminum/Polyester Shield  
Drain Wire  
Plenum



\*Product images are for illustrative purposes only and may differ from the actual product.

### Category Conductor Description:

- Twisted pairs with overall foil shield

### Category Insulation Description:

- Low smoke Polyvinyl Chloride (PVC)

### Shield Drain:

- Overall aluminum/polyester foil shield with 100% coverage

### Category Jacket Description:

- Plenum, low smoke Polyvinyl Chloride (PVC)

### Applications:

- Signal and control applications

### Standards:

- CMP/CL3P

Color Code Chart	
# of Pairs	Color
1	Black & Red
2	Black & White
3	Black & Green
4	Black & Blue
5	Black & Yellow
6	Black & Brown
7	Black & Orange
8	Red & White
9	Red & Green
10	Red & Blue
11	Red & Yellow
12	Red & Brown

13	Red & Orange
14	Green & White
15	Green & Blue
16	Green & Yellow
17	Green & Brown
18	Green & Orange
19	White & Blue
20	White & Yellow

Part Number Table

Part#	Gauge	Pairs	Stranding	Insulation Thickness	Jacket Thickness	Outside Diameter Inches	Material Weight (Lbs./M')
G132202	22	2	7x30	0.008	0.014	0.153	18.1
G132203	22	3	7x30	0.008	0.014	0.199	25.5

Note: The data shown is approximate and subject to standard industry and manufacturer tolerances

Selling Exclusively Through Distribution Since 1977 <sup>TM</sup> | phone: 800-292-OMNI | website: [omnicable.com](http://omnicable.com)

Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •  
St. Louis • Tampa • Toronto

© 2020 Omni Cable LLC