

22 AWG - Multi-Pair - Plenum Jacket

Individually Shielded Pairs
Aluminum/Mylar Shield
Plenum Rated
Plenum

Security and Alarm Cable



*Product images are for illustrative purposes only and may differ from the actual product.

Category Conductor Description:

- Stranded Bare copper

Category Insulation Description:

- Low smoke Polyvinyl Chloride (PVC)

Shield Drain:

- Aluminum/Mylar shielded pairs with one drain wire per pair

Category Jacket Description:

- Plenum, low smoke Polyvinyl Chloride (PVC)

Applications:

- Signal and control applications

Standards:

- CMP/CL3P

PART NUMBER TABLE							
Part#	Gauge	Pairs	Stranding	Insulation Thickness	Jacket Thickness	Outside Diameter Inches	Material Weight (Lbs./M')
G152202	22	2	7x30	0.008	0.014	0.148	21.1
G152203	22	3	7x30	0.008	0.014	0.202	36

Note: The data shown are approximate and subject to standard industry and manufacturer tolerances.

Selling Exclusively Through Distribution Since 1977™ | phone: 800-292-OMNI | website: omnicable.com
Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco •
Seattle • St. Louis • Tampa • Toronto
© 2020 Omni Cable LLC